




TECHNICAL CHARACTERISTICS













wineo 1000 Multi-Layer to click

Long-lasting multi-layer flooring according to EN 16511 for glueless installation without the addition of chlorin, without plasticisers or solvents

WINEO

	wood L	wood XL	stone L
Format	1288 x 187 mm	1520 x 238 mm	636 x 319 mm
Product thickness	9 mm	9 mm	9 mm
Weight	~ 8.70 kg/m ²	~ 8.70 kg/m ²	~ 8.70 kg/m ²
Profile connection	Fold-Down 	Fold-Down 	LocTec 
Planks / m² per box	8 / 1.93 m ²	6 / 2.17 m ²	9 / 1.83 m ²
Boxes / m² per pallet	44 / 84.92 m ²	48 / 104.16 m ²	60 / 109.80 m ²
Guarantee	30 years – Guarantee for private use according to Windmüller warranty conditions – www.wineo.de		



Classification		Product composition
 Utilization class 23 EN ISO 10874	Domestic area with intensive usage	1 Top element PU-top layer with NatureSurface, decor und stabilisation with ecuran
 Utilization class 32 EN ISO 10874	Commercial sector with average usage	
 R9 Anti slip category DIN 51130	R 9	2 Profile connection Fold-Down locking (wood) LocTec locking (stone)
 Resistance to staining EN 438-2	Group 1, 2 + 3: grade 5	
 Light fastness EN ISO 105-B02	Light fastness (method 2) ≥ 6	3 Core board Swell-protected Aqua- Protect HDF core board
 Residual indentation EN ISO 24343-1	≤ 0.1 mm	
 Castor chair test EN 425	25000 revolutions no damage with rolls type W	4 Underlay Integrated underlay soundPROTECT for an impact sound reduction of up to 15 dB
 Thermal resistance EN 12667	0.06 (m ² K)W	
 sound PROTECT Impact sound reduction EN ISO 10140	~ 15 dB	  PREMIUM
 sound PROTECT Reflected walking sound reduction	~ 29 %	
REACH	free from SVHC substances ≥ 0.1 %	
Disposal	<u>Private:</u> possible with normal domestic refuse <u>Commercial:</u> Refuse-key-no. AVV 170203	



Information representative des émissions dans l'air intérieur des substances volatiles présentant un risque de toxicité par inhalation, sur une échelle de classe allant de C (fortes émissions) à A+ (très faibles émissions)

Relevant Information:

- Underfloor heating: Suitable for all conventional hot water underfloor heating and electrical systems regulated up to a surface temperatur of 27 °C.
- Cleaning and care: See separate cleaning & care instruction.
- Technical subjects can be changed by Windmüller GmbH.