

TECHNICAL CHARACTERISTICS

PURLINE organic flooring | wineo 1200 to click (Semi-Rigid)

Permanently elastic polyurethane flooring according to EN 16776
Without the addition of chlorin, without plasticisers or solvents.

wineo

	wineo 1200 wood XL V4	wineo 1200 stone XL	
Format	1507 x 246 mm	1000 x 500 mm	
Product thickness	5 mm	5 mm	
Weight	9 kg/m ²	9 kg/m ²	
Profile connection	Fold-Down	LocTec	
Planks / m² per box	6 / 2.22 m ²	6 / 3.00 m ²	
Boxes / m² per pallet	48 / 106.56 m ²	36 / 108.00 m ²	
Guarantee	30 years – Guarantee for private use according to Windmüller warranty conditions – www.wineo.de		

Classification		Product composition
	Utilization class 23 EN ISO 10874	Domestic area with intensive usage
	Utilization class 33 EN ISO 10874	Commercial sector with heavy usage
	Scratch resistance EN 16776, annex A	Utilization class 33: ≥ 6 N
	Anti slip category DIN 51130	R 9
	Staining and chemical resistance EN ISO 26987	Very good resistance according to the concentration and residence time
	Light fastness EN ISO 105-B02	~ 7
	Residual indentation EN ISO 24343-1	≤ 0.10 mm
	Effect of a furniture leg EN 424	in test: Foot type 2 – no visible change
	Castor chair test EN ISO 4918	25000 revolutions no damage with rolls type W
	Thermal resistance ISO 8302	0.01 (m ² K)/W
	Impact sound reduction EN ISO 10140	in test
	Dimension stability EN ISO 23999	≤ 0.15 %
	REACH	free from SVHC substances ≥ 0.1 %
	Disposal	<u>Private:</u> possible with normal domestic refuse <u>Commercial:</u> Refuse-key-no. AVV 170203
		1 Top element <ul style="list-style-type: none"> • PU-top layer with surface structure • decor paper • stabilisation
		2 Profile connection wood XL – Fold-Down stone XL – LocTec
		3 Base layer ecuran high performance composite material Tele-Stop feature
		4 Backing Integrated Fleece TEC-System
		wood XL V4 joint lacquered
		 www.blauer-engel.de/liz120

Windmüller GmbH
 Nord-West-Ring 21
 D-32832 Augustdorf
 DOP: 2001010
 EN 14041:2004 / AC2006
 1658

 www.wineo.de

ÉMISSIONS DANS L'AIR INTÉRIEUR

 Information représentative des émissions dans l'air intérieur des substances volatiles présentant un risque de toxicité par inhalation, sur une échelle de classe allant de C (fortes émissions) à A+ (très faibles émissions)

DGNB NAVIGATOR
 Registrierungs-Code
 NAPCCU
 www.dgnb-navigatord.de

GREENGUARD
 GOLD

THE INDOOR CLIMATE LABEL

basis
 eco-bau

EPD
 THIRD-PARTY VERIFIED
 Institut Bauen und Umwelt e.V.

floor score
 CERTIFIED BY SCS Global Services

M1
 EMISSION CLASS FOR BUILDING MATERIAL

Relevant Information:

- Underfloor heating: Suitable for all conventional hot water underfloor heating and electrical systems regulated up to a surface temperatur of 27 °C.
- Cleaning and care: See separate cleaning & care instruction.
- Technical subjects can be changed by Windmüller GmbH.