

Allclean

Surface cleaner

► Professional quality

Features

- Universal surface cleaner
- Dissolves grease quickly
- Safe cleaning
- Evaporates very quickly
- Leaves behind no oil film
- Powerful solvent effect
- Does not attack materials

Benefits of use

- Removes tar, oil, putty, grease, silicone, adhesive, corrosion protection agents etc. quickly and safely
- ▶ Time saving
- Suitable for use on plastics, metals, glass, painted surfaces etc.
- Also for acrylic

Areas of application

- Pre-cleaning of surfaces which are bonded with beko products, e.g. ALLCON 10, Tackcon, Allbond-Fluid etc.
- Removes surplus unhardened PU adhesive,
 e.g. ALLCON 10, Tackcon, Fibcon, from surfaces without smearing
- For the removal of adhesive residues from protective films and labels, including on acrylic baths
- Effortlessly removes sealant residues in motor vehicles and heating/sanitation systems
- Can be used to clean cable ends (e.g. when fitting shrink sleeves)





beko <-

Allclean







Allclean

Surface cleaner

Content 500 ml Art.-No. 266 120 0500EN

Content 100 ml

Art.-No. 266 120 0100EN

Range of use

- Motor vehicle trade
- Print shops
- ▶ Paint shops
- ▶ Industrial enterprises
- ► Painting and decorating
- Petrol stations
- ▶ Building trade
- ▶ Wood trade

Directions for use

Put some **beko Aliclean** on a soft, clean cloth. Wipe the surface to be cleaned, applying light pressure. Dry off with a soft cloth. If required, repeat the process. Check surfaces for colour fastness.

Caution

- Treat freshly painted surfaces with care.
- Test small areas before general use.
- Do not apply to leather or waxed surfaces.
- ▶ Keep out of the reach of children.
- Do not ingest or breathe in.
- Avoid contact with skin and eyes.
- Protect clothing.
- In the case of incorrect or improper application, any product warranty becomes void.
- For professional and industrial use only.
- Please observe safety data sheet.

Technical data				
Basis	Dearomatised hydrocarbon			
Colour	transparent			
Smell	characteristic			
Density	approx. 0,75 g/cm³			
Viscosity	low viscosity			
Storage life	24 months			
Storage	in well sealed containers, cool and dry			
Contents/ packaging	Can 500 ml Can 250 ml Can 100 ml	6 pcs/box 12 pcs/box 24 pcs/box	756 pcs/pallet 960 pcs/pallet 3024 pcs/pallet	ArtNo. 266 120 0500EN ArtNo. 266 120 0250EN ArtNo. 266 120 0100EN

This publication supersedes all previous editions and renders the latter invalid.

Currently valid documents (safety data sheet) can be viewed on www.beko-group.com!

Subject to technical changes! Print date: 02/2022 Art.-No. 266 120 9EN

